SS-CN367T/MS367T

SERVICE MANUAL

US Model
Canadian Model

Ver 1.0 2004. 03

SS-CN367T SS-MS367T

• SS-CN367T (center speaker) and SS-MS367T (front, surround and surround back speaker) are the speaker section in SA-VE367T.

SPECIFICATIONS

SS-MS367T (front, surround and surround back speakers)

Speaker system	2 way, magnetically shielded
Speaker units	Woofer: 9 cm (3 1/2 in.)
	Tweeter: 1.3 cm (1/2 in.)
Enclosure type	Bass reflex
Rated impedance	8 ohms
Power handling capacity	
Maximum input power:	120 watts
Sensitivity level	84 dB (1 W, 1 m)
Frequency range	100 Hz - 27,000 Hz
Dimensions (w/h/d)	Approx. 112 × 150 × 132 mm
	(4 3/16 × 5 3/8 × 5 1/16 in.)
Mass	Approx. 1 kg (2 lb 4 oz) each

SS-CN367T (center speaker)

Speaker system	2 way, magnetically shielded
Speaker units	Woofer: 9 cm (3 1/2 in.)
	Tweeter: 1.3 cm (1/2 in.)
Enclosure type	Bass reflex
Rated impedance	8 ohms
Power handling capacity	
Maximum input power:	120 watts
Sensitivity level	84 dB (1 W, 1 m)
Frequency range	100 Hz - 27,000 Hz
Dimensions (w/h/d)	Approx. 200 × 112 × 115 mm
	(7 3/8 × 4 3/16 × 4 3/16 in.)
Mass	Approx. 1.1 kg (2 lb 7 oz)

Design and specifications are subject to change without notice.

PARTS LIST

Part No.	Description	Remark
A-4713-931-A	OVERALL ASSY (SS-MS367T)	
A-4713-933-A	OVERALL ASSY (SS-CN367T)	

SPEAKER SYSTEM

9-877-697-01
2004C04-1
© 2004. 03
Sony Corporation
Home Audio Company
Published by Sony Engineering Corporation

SONY®

REVISION HISTORY

Clicking the version allows you to jump to the revised page.
Also, clicking the version at the upper on the revised page allows you to jump to the next revised page.

Ver.	Date	Description of Revision
1.0	2004. 03	New